

Paramétrage des poêles à granulés
le 15/12/2006

Paramètres A9	Vestalis	Lohic	Giboulée	Kerdonis	Titan
Références poêles	C07740.06-DA-A	C07741.02-DA	C07744.01-DA	C07742.03-DA	C07743.02-DA
Vis sans fin	φ 50 φ 15	φ 50 φ 15	φ 50 φ 15	φ 50 φ 15	φ 80
PR 01	15'	15'	15'	15'	15'
PR 02	06'	06'	06'	06'	06'
PR 03	60'	60'	90'	90'	60'
PR 04	2,0"	2,0"	2,0"	2,3"	1,1"
PR 05	1,8"	1,8"	1,8"	2,0"	0,7"
PR 06	1,5"	1,5"	1,5"	1,5"	0,7"
PR 07	2,0"	1,9"	2,0"	2,2"	0,9"
PR 08	2,6"	2,3"	2,6"	2,9"	1,2"
PR 09	3,2"	2,7"	3,2"	3,6"	1,6"
PR 10	3,8"	3,2"	3,8"	4,5"	2,2"
PR 11	60"	60"	60"	60"	
PR 12	30"	30"	30"	30"	5°C
PR 13	45°C	45°C	45°C	45°C	45°C
PR 14	250°C	250°C	250°C	250°C	250°C
PR 15	100°C	100°C	100°C	100°C	40°C
PR 16	13	13	13	16	17
PR 17	14	14	14	23	25
PR 18	08	07	09	08	08
PR 19	09	07	10	09	09
PR 20	10	07	10	10	10
PR 21	11	07	10	11	11
PR 22	12	07	10	12	11
PR 23	08	08	08	08	5'
PR 24	09	09	09	10	5"
PR 25	11	11	11	11	
PR 26	12	12	12	12	
PR 27	13	13	13	13	
PR 28	120°C	120°C	120°C	120°C	120°C

Paramètres B9

PR 39				10	
PR 40				11	
PR 41				12	
PR 42				14	
PR 43				16	

Felipe PLAZA
Romita DANCIU
Andrea La Vella