

```

1  #include <iostream>
2  #include <vector>
3  #include <cmath>
4  #include <gmp.h>
5  #include <stdlib.h>
6  #include <errno.h>
7  #include <limits.h>
8  typedef unsigned int uint;
9  using std::cout;
10 using std::cerr;
11 using std::endl;
12 using std::cin;
13 using std::vector;
14
15 void usage (const char *program_name) {
16     cerr << "Usage : " << program_name << " integer" << endl;
17 }
18
19 vector<uint> *primes_list (uint n)
20 {
21     vector<uint> *list = new vector<uint> ();
22     if (n < 2) { return list; }
23
24     list->push_back (2);
25
26     for (uint k = 3; k <= n; k += 2) {
27         double sqrt_k = sqrt(k);
28         bool is_prime = true;
29         vector<uint>::iterator iter;
30         for (iter = list->begin(); *iter <= sqrt_k; iter++) {
31             if (k % *iter == 0) {
32                 is_prime = false;
33                 break;
34             }
35         }
36
37         if (is_prime) {
38             list->push_back (k);
39         }
40     }
41
42     return list;
43 }
44
45 int main (int argc, char **argv)
46 {
47     if (argc < 2) {
48         usage (argv[0]);
49         exit(EXIT_FAILURE);
50     }
51
52     char *str = argv[1];
53     char *endptr;
54     errno = 0;
55     long n = strtol (str, &endptr, 10);
56
57     if ((errno == ERANGE && (n == LONG_MAX || n == LONG_MIN))
58         || (errno != 0 && n == 0)) {
59         perror("strtol");
60         exit(EXIT_FAILURE);
61     }
62
63     if (endptr == str) {
64         usage (argv[0]);
65         exit(EXIT_FAILURE);
66     }
67
68     vector<uint> *list = primes_list (n);
69     mpz_t primorielle;
70     mpz_init (primorielle);
71     mpz_set_si (primorielle, 1);
72     vector<uint>::iterator iter;
73
74     for (iter = list->begin(); iter != list->end(); iter++) {
75         mpz_mul_si (primorielle, primorielle, *iter);
76     }
77
78     gmp_printf ("%Zd\n", primorielle);
79     delete list;
80     mpz_clear (primorielle);
81
82     return EXIT_SUCCESS;
83 }

```