


U3280M Transponder Front-End IC

U9280M Microcontroller with Transponder Front End



The **U3280M** is a transponder interface for contactless ID systems, remote control systems, tag and sensor applications. Batteryless applications are also possible. The device enables to create customized algorithms and data transfer protocols. Compatible to smart sensors.

The **U9280M** is a multi-chip module for remote control and contactless ID systems consisting of the microcontroller M44C092 and the U3280M transponder interface circuit with EEPROM.

U3280M

Adjustable analog front end IC U3280M for 120-134-kHz transponder applications with microcontroller. It supplies the microcontroller with power from an RF field via the LC-resonant circuit and enables contactless bidirectional data communication via this RF field. The intelligent power management handles the switching between magnetic field and battery power supply. To store permanent data like identifier code and configuration data, the U3280M includes a 512-bit EEPROM with serial interface.

Features U3280M

- Contactless power supply and communication interface
- Up to 10 kbaud data rate (R/O)
- Power management for contactless- and battery power supply
- Frequency range 100 to 150 kHz
- 32 x 16-bit EEPROM
- Two wire serial interface
- Shift register supported Biphase and Manchester modulator stage
- Reset I/O line
- Field clock extractor
- Field and gap detection output for wake up and data reception
- Field modulator with energy-saving damping stage

Atmel Corporation
2325 Orchard Parkway
San Jose, Ca 95131, USA
TEL (1) 408 441 0311
FAX (1) 408 487 2600

Atmel Wireless & Microcontrollers
Theresienstrasse 2
P.O.B. 3535
D-74025 Heilbronn
Germany
TEL (49) 71 31/67 25 94
FAX (49) 71 31/67 24 23

Main Sales Offices

France
TEL (33) 1 30 60 70 00

Germany
TEL (49) 71 31 67 36 36

Italy
TEL (39) 02 38 03 71

Spain
TEL (34) 91 564 51 81

Sweden
TEL (46) 8 587 48 800

United Kingdom
TEL (44) 1 344 707 300

USA-Eastern
TEL (1) 908 848 5208

USA-Western
TEL (1) 408 441 0311

Hong Kong
TEL (852) 23 789 789

Korea
TEL (822) 785 1136

Singapore
TEL (65) 260 8223

Taiwan
TEL (886) 2 2609 5581

Japan
TEL (81) 3 3523 3551

Web Site
<http://www.atmel-wm.com>



Ref.: U3280M/U9280M/1001 -
© Atmel Germany GmbH - 2001

Atmel, the Atmel logo and combinations thereof and others contained herein, are trademarks of Atmel Corporation. Terms and product names in this document may be the trademarks of others.



U9280M

The U9280M is a fully programmable multi-chip module for remote control and contactless ID systems when the implementation of both transponder algorithms and IR/RF protocols are required. It consists of the 4-bit microcontroller M44C092 and U3280M transponder interface circuit with EEPROM. A wide range of customer-specific solutions (e.g., combination with bi-directional interfaces) can be realized. The μ C supports with its built-in timers many kinds of IR- and RF-transmission modes such as burst-modulation modes, PWM-, NRZ-, Manchester- and Biphase coding.

Features U9280M

- 4-bit HARVARD architecture
 - 4 k x 8-bit application ROM, 256 x 4-bit RAM
 - 32 x 16-bit EEPROM
 - 10 bidirectional I/Os
 - 4 external interrupt inputs (SSO20), 8 interrupt levels
 - 2 x 8-bit multifunction timer/counter
 - Interval timer with watchdog
 - Two-wire serial interface
 - On-chip RC oscillator
 - On-chip crystal oscillator
 - Contactless power supply and communication interface
 - Power management for contactless- and battery-power supply
 - Shift-register-supported modulator and demodulator stages
 - Low power consumption
 - Active mode < 300 μ A @ 2 V and 1 MHz system clock frequency (2 μ s instruction cycle)
 - Power-down mode < 1 μ A
 - Supply voltage 2.0 V to 6.5 V
 - High-level language programming in qFORTH
 - Operating speed: 1 – 10 μ s instruction cycle (2 μ s @ $V_{DD} = 2$ V)
-
- Application kit TMEB8704 for reader and transponder ICs
 - Data sheets
 - QualIPacks