



- R1:** 68K **R17:** 47ohm **C1:** .047uF-400V **C16:** .047uF-600V
R2: 100K **R18:** 220K **C2:** 200pf **C17:** .047uF-600V
R3: 470K **R19:** 100K-1W **C3:** 25uF-25V P **C18:** 25uF-25V P
R4: 1.5Mo **R20:** 100K-1W **C4:** - **C19:** 32uF-32uF P
R5: 220K **R21:** 470K **C5:** .003uF **C20:** 8uF-500V P
R6: 4.7K **R22:** 470K **C6:** - **C21:** .01uF-500V
R7: 3.3K **R23:** 27K **C7:** .02uF **C8:** 0.47uF-400V
R8: 27K **R24:** 47ohm **C9:** 25uF-25V P **C9:** 25uF-25V P
R9: 100K **R25:** 4.7K **C10:** .22uF-400V
R10: 2.2K **R26:** 4.7K **C11:** .02uF-150V
R11: 1Mo **R27:** 47ohm **C12:** .001uF
R12: 220K **R28:** 130ohm - 2W
R13: 47K **R29:** 1K **C13:** .001uF
R14: 220K **R30:** 500ohm-10W **C14:** 32uF-32uF P
R15: 15K **R31:** 4.7K-2W **C15:** 25uF-25V P
R16: 22K **R32:** 10K-1W
- TR1:** OUTPUT TRANSFORMER
TR2: MAINS TRANSFORMER
RL1: MUTING RELAY
VR1: VOLUME CONTROL
VR2: BASS EMPHASIS CONTROL
VR3: TREBLE EMPHASIS CONTROL
PL.1, SO.1: 2 WAW. PICKUP INPUT
PL.2, SO.2: 5 WAW VOLUME CONTROL
PL.3, SO.3: 5 WAW SPEAKER 15 OHM/IMPEDENCE
PL.4, SO.4: 5 WAW SPEAKER 7 O INT & EXT
V51: MAINS VOLTAGE SELECTOR 200,220,240, AC ONLY
PL.5, SO.5, 6: WAW. MAINS, RELAY, INDICATOR LAMPS.
- S05:** SOCKET CONNECTIONS VIEW CABLE END
 1- RED MAINS LIVE
 2- BROWN INDICATOR LAMPS
 3- GREEN EARTH
 4- BLACK MAINS NEUTRAL
 5- BLUE RELAY RETURN
 6- BROWN & WHITE INDICATOR LAMPS
- ALL RESISTOR 1/2 WATT 20% UNLESS OTHERWISE STATED

