2) 4-bit interface mode (Condition: fosc = 270KHZ)

Power on

Wait for more than 30 ms after Vdd rises to 4.5 v

Function set

RS	R/W	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0
0	0	0	0	1	0	X	X	X	X
0	0	0	0	1	0	X	X	X	X
0	0	N	F	X	X	X	X	X	X

N	0	1-line mode
	1	2-line mode
F	0	display off
	1	display on

Wait for more than 39 µs

Display ON/OFF Control

RS	R/W	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0
0	0	0	0	0	0	X	X	X	X
0	0	1	D	C	B	X	X	X	X

D	0	display off
	1	display on
C	0	cursor off
	1	cursor on
B	0	blink off
	1	blink on

Wait for more than 39 µs

Display Clear

RS	R/W	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0
0	0	0	0	0	0	X	X	X	X
0	0	0	0	0	1	X	X	X	X

Wait for more than 1.53 ms

Entry Mode Set

RS	R/W	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0
0	0	0	0	0	0	X	X	X	X
0	0	0	1	I/D	SH	X	X	X	X

I/D	0	decrement mode
	1	increment mode
SH	0	entire shift off
	1	entire shift on

Initialization end