

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 666902

Jameco Part No.	Cross Ref.	Model No.	MAX. Applied Voltage		MAX. Energy	MAX. Peak Current	Rated Wattage	Clamping Voltage		Varistor	Typical Capacitance			
			Continuous		(2ms)	(8/20 μ s)				v0.1mA	1kHz			
			Acrms (V)	DC (V)	(J)	(A)	(W)	(A)	(V)	(V)	(pF)			
666751	V18ZA2	DNR10D180K	11	14	1.5	500/1 time 250/2 times	0.05	5	36	18 (16-20)	7500			
666806	V22ZA2	DNR10D220K	14	18	2.04				43	22 (20-24)	6000			
		DNR10D270K	17	22	2.5				63	27 (24-20)	4000			
		DNR10D330K	20	26	3.06				65	33 (30-36)	3000			
		DNR10D390K	25	31	3.5				77	39 (35-43)	2600			
666865	V47ZA3	DNR10D470K	30	38	4.5				93	47 (42-45)	2200			
		DNR10D560K	35	45	5.5				110	56 (50-62)	1800			
666902	V68ZA3	DNR10D680K	40	56	6.5				135	68 (61-75)	1800			
666929	V82ZA4	DNR10D820K	50	65	8				2500/1 time 1250/2 times	0.4	25	135	82 (74-90)	1800
		DNR10D101K	60	85	10							165	100 (90-110)	1400
		DNR110D121K	75	100	12	200	120 (108-132)	1100						
		DNR10D151K	95	125	16	250	150 (135-165)	900						
666970	V180ZA5	DNR10D181K	115	150	18	300	180 (162-198)	660						
		DNR10D201K	130	170	20	340	200 (180-220)	500						
		DNR10D221K	140	180	23	360	220 (198-242)	450						
		DNR10D241K	150	200	25	395	240 (216-264)	400						
		DNR10D271K	175	225	30	455	270 (243-297)	350						
		DNR10D331K	210	275	30	550	330 (297-363)	315						
		DNR10D361K	230	300	35	595	360 (324-396)	300						
		DNR10D391K	250	320	40	650	390 (351-429)	270						
		DNR10D431K	275	350	45	710	430 (387-473)	250						
		DNR10D471K	300	385	45	775	470 (423-517)	230						
		DNR10D561K	250	455	45	925	560 (504-616)	190						
		DNR10D621K	385	505	45	1025	620 (558-682)	130						
		DNR10D681K	420	560	45	1120	680 (612-748)	130						
		DNR10D751K	460	615	50	1240	750 (675-825)	120						
		DNR10D781K	485	640	50	1290	780 (702-858)	120						
		DNR10D821K	510	670	55	1355	820 (738-902)	110						
		DNR10D911K	550	745	60	1500	910 (819-1001)	100						
		DNR10D102K	625	825	65	1650	1000 (900-1100)	90						
		DNR10D112K	680	895	70	1815	1110 (990-1210)	80						
		DNR10D112K	680	895	70	1815	1110 (990-1210)	80						