



TECHNICAL DATA:

Valve type: XHD2

Function: 2/2 NC

Ports: NPT 1/4"

Orifice size: 1.0 mm

Pressure range: 0 - 500 bar

kv: 0.3 (l/min, water at 1 bar)

Minimum fluid temperature: -40°C

Valve body: AISI 316L (EN 1.4404)

All metal pressure retaining parts: AISI 316L (EN 1.4404)

Main seal: PCTFE

O-ring: FPM ED resistant

Coil type: Ex35P II 2 G Ex eb mb IIC T5 Gb

Voltage: 24 V AC/DC

Power: 4 W

Order code: 326781

Tolerances to ISO 2768-1 medium		Date	Name	Signature	Issue No. 1	Material:
	Drawn	2024-03-21	A. Jakša		Notification 1134	
	Checked				Date 2024-03-21	JAKŠA d.o.o. PHONE: +386 1 5373 066 - FAX: +386 1 5373 067 Štandrova 8, SI-1231 Ljubljana-Črnuče, SLOVENIA
	Approved					
Title: XHD2 NPT1/4 1 PCT 500b 24V ExP						Page: 1/1 Doc. no.: 8031 Code: AJ326781
Scale: 1:2	This drawing is a confidential property of JAKŠA d.o.o. Not to be handed over to, copied or used by third party.					